Superior Chemistry. **Superior Performance.**

Multi-Vehicle Transmission Fluid

Printed On: May 19, 2013

Benefits of Mag 1 Multi-Vehicle ATF include:
•Excellent high and low temperature protection
•Stable friction properties for smooth and consistent shifting
•Excellent sheer stability
•Suitable for use in Chrysler automatic transmissions requiring the 3 and 4 Chrysler automatic transmission fluids

INSPECTION INFORMATION	TEST METHOD	TYPICAL VALUE
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8601
Viscosity @ 40°C cSt	ASTM D445	35.43
Viscosity @ 100°C cSt	ASTM D445	7.56
Pour Point °C (°F)	ASTM D5950	-51°C (-60°F)
Viscosity Index	ASTM D2270	189
Color	ASTM D 1500	Red
Gravity, °API	ASTM D287	33.02
Brookfield Viscosity at -40°C, cP	ASTM D2983	11,300

Superior Chemistry. **Superior Performance.**

MAG1®

CLAIMS INFORMATION

Printed On: May 19, 2013

Allison C-4	Approved
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
Dexron III, Dexron II, Dexron	Suitable for Use
Honda DW-1, Z-1	Suitable for Use
Hyundai/Kia SP-II and SP-III	Suitable for Use
Hyundai SP-IV	Suitable for Use
Idemitsu K17	Suitable for Use
JWS 3309	Suitable for Use
M315-2004 JASO 1A	Approved
MAN 339 Type Z1, V1	Meets Requirements
MAN 339 Type Z2	Meets Requirements
Mazda ATF M-III, MV	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
Mercon V	Approved
Mercon, Ford ESP-M2C166-H	Suitable for Use
Mitsubishi Diamond SP-II, SP-III, J2	Suitable for Use
Nissan Matic-D, J, K, 402	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Toyota T-III, T-IV, WS, Ford XT8QAW	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo Passenger Car (4 – 6 sp), Volvo 97340, 97341	Suitable for Use
VW G 052 025, 162, 099, 055 025	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use
ZF TE-ML 14B	Meets Requirements

JWS 3309